



# Safety Data Sheet

---

## SECTION 1: IDENTIFICATION OF THE MATERIAL AND SUPPLIER

---

### PRODUCT NAME:

**Fuel Doctor**

### RECOMMENDED USE:

Fuel Treatment

### SUPPLIER DETAILS:

Company:	Fuel Doctors Australia Pty Ltd
Address:	30 Rosa Street, Richlands, Qld 4077, Australia
Telephone Number:	(+61-7) 3217 0077
Facsimile Number:	(+61-7) 3375 4400
Emergency Telephone No:	(+61-7) 3217 0077 (Office Hours) (+61-4)12 211 777 (After Hours)

---

## SECTION 2: HAZARDS IDENTIFICATION

---

Not currently classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail; **NON-DANGEROUS GOODS.**

This product is classified as hazardous according to Safe Work Australia; **HAZARDOUS SUBSTANCE.**

### Classification of the substance or mixture:

Serious eye damage/eye irritation: Cat. 1  
Hazardous to the aquatic environment - acute: Cat. 2  
Hazardous to the aquatic environment - chronic: Cat. 3

### SIGNAL WORD: DANGER



### Hazard Statement(s):

H318 Causes serious eye damage.  
H412 Harmful to aquatic life with long lasting effects.  
H401 Toxic to aquatic life.

### Precautionary Statement(s)

#### Prevention

P264 Wash hands thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective gloves / protective clothing / eye protection / face protection.

#### Response

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310: Immediately call a POISON CENTER or doctor/physician.

#### Storage

No storage statements.

#### Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### Poisons Schedule (SUSMP)

S5 CAUTION

---

**SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS**

---

<b>MATERIAL/COMPONENT</b>	<b>CAS Number</b>	<b>Proportion</b>
2-(2-butoxyethoxy)ethanol	112-34-5	>30%<60%
Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-, branched	69011-36-5	>10%<30%
Alcohols, C12-14, ethoxylated	68439-50-9	>10%<30%
Ingredients not classified as hazardous		to 100%

---

**SECTION 4: FIRST AID MEASURES**

---

**For advice, contact a Poisons Information Centre (Phone e.g. Australia 131 126; New Zealand 0 800 764766) or a doctor.**

**Inhalation:**

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. Seek medical attention.

**Skin Contact:**

If skin contact occurs, remove contaminated clothing and wash skin with running water. If irritation occurs seek medical advice

**Eye Contact:**

If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.

**Ingestion:**

Immediately rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water. If vomiting occurs give further water. Seek medical advice.

**Indication of immediate medical attention and special treatment needed:**

Treat symptomatically. Can cause corneal burns.

---

**SECTION 5: FIRE FIGHTING MEASURES**

---

**Suitable Extinguishing Media:**

Fine water spray, normal foam, dry agent (carbon dioxide, dry chemical powder).

**Unsuitable Extinguishing Media:**

Water jet.

**Specific hazards arising from the substance or mixture:**

Combustible liquid.

**Special protective equipment and precautions for fire-fighters:**

On burning will emit toxic fumes, including those of oxides of carbon . Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion. Keep containers cool with water spray. If safe to do so,remove containers from path of fire.

---

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

---

**Emergency procedures/Environmental precautions:**

Shut off all possible sources of ignition. Clear area of all unprotected personnel. If contamination of sewers or waterways has occurred advise local emergency services.

**Personal precautions/Protective equipment/Methods and materials for containment and cleaning up:**

Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contact and breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal. Wash area down with excess water. High risk of slipping due to leakage/spillage of product. Forms slippery surfaces with water.

---

**SECTION 7: HANDLING AND STORAGE**

---

Classified as a C2 (COMBUSTIBLE LIQUID) for the purpose of storage and handling, in accordance with the requirements of AS 1940. Refer to State Regulations for storage and transport requirements.

This material is a Scheduled Poison S5 and must be stored, maintained and used in accordance with the relevant regulations.

**Precautions for safe handling:**

Avoid skin and eye contact and breathing in vapour. When using do not eat, drink or smoke. Wash hands before breaks and at the end of the work day. Keep out of reach of children.

**Conditions for safe storage, including any incompatibilities:**

Store in a cool, dry, well ventilated place Store away from sources of heat or ignition. Store away from incompatible materials described in Section 10. Store away from foodstuffs. Keep containers closed when not in use - check regularly for leaks.

---

## SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

---

### Control Parameters:

No value assigned for this specific material by Safe Work Australia.

### Engineering Controls:

Ensure ventilation is adequate and that air concentrations of components are controlled below quoted Workplace Exposure Standards. Vapour heavier than air - prevent concentration in hollows or sumps. DO NOT enter confined spaces where vapour may have collected. Keep containers closed when not in use.

If in the handling and application of this material, safe exposure levels could be exceeded, the use of engineering controls such as local exhaust ventilation must be considered and the results documented. If achieving safe exposure levels does not require engineering controls, then a detailed and documented risk assessment using the relevant Personal Protective Equipment (PPE) (refer to PPE section below) as a basis must be carried out to determine the minimum PPE requirements.

### Individual Protection Measures, for example Personal Protective Equipment (PPE):

The selection of PPE is dependent on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

OVERALLS, SAFETY SHOES, CHEMICAL GOGGLES, GLOVES, RESPIRATOR.

Wear overalls, chemical goggles and impervious gloves. If determined by a risk assessment an inhalation risk exists, wear an organic vapour respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

---

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

---

Boiling Range (C):	>230	Melting Point(C):	Not determined
VAP Press(hPa):	<0.1	Odour:	Faint
Specific Gravity:	0.93 -0.95	VAP Density:	Not determined
Sol In Water (g/l):	Dispersable	Appearance:	Green Liquid
pH:	6.0 – 7.5	Evaporation Rate :	Not determined
Flash Point (C) (Closed cup):	>100	Density (g/L):	0.94 – 0.95

---

## SECTION 10: STABILITY AND REACTIVITY

---

### Reactivity:

No information available

### Chemical stability:

Stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

### Possibility of hazardous reactions:

Contact with aluminium or alloys containing aluminium may result in alcoholate formation with subsequent evolution of hydrogen.

### Conditions to avoid:

Oxidising agents, excessive heat will lead to accelerated oxidative degradation,

### Incompatible materials:

Incompatible with aluminium and alloys , copper , copper alloys , neoprene ,natural rubber , oxidising agents , acids , alkalis, halogens, reactive chemicals.

### Hazardous decomposition products:

Toxic fumes of carbon oxides on combustion or oxidation.

---

## SECTION 11: TOXICOLOGY INFORMATION

---

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

### Acute Toxicity/Effects

#### Oral

LD50 (rat) > 4,000 mg/kg Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkenness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.

### Irritation / corrosion

Assessment of irritating effects: Risk of serious damage to eyes. Not irritating to the skin.

**Inhalation:**

Breathing in mists or aerosols may produce respiratory irritation.

**Skin**

LD5 (rat) >2000mg/kg. Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

**Eye**

Species: rabbit Result: Severe Irritant. Method: OECD Guideline 405. Contamination of eyes can result in permanent injury

**Sensitization**

Assessment of sensitization: No data available.

**Chronic Toxicity/Effects**

Repeated dose toxicity

Assessment of repeated dose toxicity: No data available.

**Genetic toxicity**

Assessment of mutagenicity: No data available

---

**SECTION 12: ECOLOGICAL INFORMATION**

---

**Ecotoxicity**

Avoid contaminating waterways.

**Toxicity**

Toxicity to fish

LC50 (96 h) 2 - 20 mg/l, *Leuciscus idus*

Aquatic invertebrates

EC50 (48 h) 0.2- 2 mg/l, *Daphnia magna*

Aquatic plants

EC50 (72 h) 0.2 - 2 mg/l (growth rate), *Scenedesmus subspicatus*

**Microorganisms/Effect on activated sludge**

Toxicity to microorganisms

bacterium/EC10 (16 h): > 10,000 mg/l

**Persistence and degradability****Elimination information**

>= 90 % Bismuth-active substance (mod. OECD 303A)

90 - 100 % DOC reduction (OECD 301 A (new version)) (aerobic, activated sludge, domestic).

Readily biodegradable.

**Mobility in soil**

No information available.

---

**SECTION 13: DISPOSAL CONSIDERATIONS**

---

**Disposal methods:**

Refer to Waste Management Authority. Dispose of contents and container in accordance with local, regional, national, international regulations.

---

**SECTION 14: TRANSPORT INFORMATION**

---

**Road and Rail Transport:**

Not currently classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for transport by Road and Rail.

**Marine Transport:**

Not currently classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

**Air Transport:**

Not currently classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

---

**SECTION 15: REGULATORY INFORMATION**

---

This product is classified as hazardous according to Safe Work Australia; **HAZARDOUS SUBSTANCE.**

**Classification of the substance or mixture:**

Serious eye damage/eye irritation: Cat. 1

Hazardous to the aquatic environment - acute: Cat. 2

Hazardous to the aquatic environment - chronic: Cat. 3

**SIGNAL WORD: DANGER**



**Hazard Statement(s):**

H318 Causes serious eye damage.  
H412 Harmful to aquatic life with long lasting effects.  
H401 Toxic to aquatic life.

**Standard Uniform Schedule of Medicine and Poisons**

Schedule 5

**Australia inventory (AICS):** All components are listed or exempted.

---

**SECTION 16: OTHER INFORMATION**

---

**Abbreviations**

**ACGIH** - American Conference of Industrial Hygienists.

**ADG** - Australian Dangerous Goods.

**atm** Atmosphere

**BEI** - Biological Exposure Index/Indices.

**CAS** Chemical Abstracts Service (Registry Number)

**cm<sup>2</sup>** Square Centimetres

**CNS** - Central Nervous System.

**CO<sub>2</sub>** Carbon Dioxide

**COD** Chemical Oxygen Demand

**deg C** Degrees Celsius

**g** Grams

**g/cm<sup>3</sup>** Grams per Cubic Centimetre

**g/l** Grams per Litre

**HSNO** Hazardous Substance and New Organism

**IARC** - International Agency for Research on Cancer.

**IDLH** Immediately Dangerous to Life and Health

**Immiscible Liquids** are insoluble in each other.

**kg** Kilogram

**kg/m<sup>3</sup>** Kilograms per Cubic Metre

**LC<sub>50</sub>** LC stands for lethal concentration. LC<sub>50</sub> is the concentration of a material in air which causes the death of 50% (one half) of a group of test animals. The material is inhaled over a set period of time, usually 1 or 4 hours.

**LD<sub>50</sub>** LD stands for Lethal Dose. LD<sub>50</sub> is the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals.

**ltr** or L Litre

**m<sup>3</sup>** Cubic Metre

**mbar** Millibar

**mg** Milligram

**mg/24H** Milligrams per 24 Hours

**mg/kg** Milligrams per Kilogram

**mg/m<sup>3</sup>** Milligrams per Cubic Metre

**Misc** or **Miscible** Liquids form one homogeneous liquid phase regardless of the amount of either component present.

**mm** Millimetre

**mmH<sub>2</sub>O** Millimetres of Water

**mPa.s** Millipascals per Second

**N/A** Not Applicable

**NIOSH** National Institute for Occupational Safety and Health

**NOHSC** National Occupational Health and Safety Commission

**NOS** Not Otherwise Specified.

**OECD** Organisation for Economic Co-operation and Development

**PEL** Permissible Exposure Limit

**Pa** Pascal

**pH** - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

**ppb** Parts per Billion

**ppm** Parts per Million

**ppm/2h** Parts per Million per 2 Hours

**ppm/6h** Parts per Million per 6 Hours

**RCP** Reciprocal Calculation Procedure

**RTECS** - Registry of Toxic Effects of Chemical Substances.

**STEL** Short Term Exposure Limit

**STOT-RE** Specific target organ toxicity (repeated exposure)

**STOT-SE** Specific target organ toxicity (single exposure)

**SWA** - Safe Work Australia.

**TLV** Threshold Limit Value

**tne** Tonne

**TWA** Time Weighted Average

**ug/24H** Micrograms per 24 Hours

**UN** United Nations

**wt** Weight

PREPARED BY: Malcolm Swanney BSc Chem  
LAST REVISION DATE: 15 November 2021  
REASON: 5 yearly update

Material Safety Data Sheets are current for a maximum of five years but may be updated more frequently. Please ensure that you have a current copy.

All information contained in this Data Sheet is as accurate and up-to-date as possible. Since Santo Australia and its subsidiary companies cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Santo Australia and its subsidiary companies will not be responsible for damages of any nature resulting from use of or reliance upon the information. No expressed or implied warranties are given other than those implied mandatorily by Commonwealth, State or Territory legislation.

---

**END OF DOCUMENT**

---